



## Mobil Super™ 1000 X1 20W-50

Mobil Passenger Vehicle Lube , Turkey

Mobil Passenger Engine Oil

### Product Description

The Mobil Super™ 1000 range of lubricants are premium mineral engine oils, designed to provide a high level of protection and performance.

### Features and Benefits

Mobil Super 1000 products are industry tested so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 X1 provides:

- Good wear protection
- Good engine cleanliness
- Good high temperature protection

### Applications

Mobil Super 1000 products have been formulated for use in nearly all vehicles. Mobil Super 1000 is suitable for:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Mobil Super 1000 X1 20W-50 is also suitable for use in LPG vehicles.

ExxonMobil particularly recommend Mobil Super 1000 for daily driving under normal conditions. Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

| <b>This product is recommended for use in applications requiring:</b> |
|---|
| API CF  |
| ACEA A3/B3-16   |
| MB 229.1  |

| <b>This product meets or exceeds the requirements of:</b> |
|---|
| API SJ  |
| API SL  |

API SM

API SN

API SN PLUS

## Properties and Specifications

| Property   |            |
|--|------------|
| Grade  | SAE 20W-50 |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 20.4       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 181        |
| Density @ 15.6 C, g/ml, ASTM D4052                         | 0.886      |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 255        |
| Pour Point, °C, ASTM D97                                   | -27        |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2024

Mobil Oil Türk A.S.

Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 850 390 4939

<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2026 Exxon Mobil Corporation. All Rights Reserved