



Mobil 1™ ESP Formula P 5W-30

Mobil Passenger Vehicle Lube , France

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1 ESP Formula P 5W-30 is an advanced performance synthetic technology engine oil designed to help provide exceptional cleaning power, wear protection and overall performance in both Diesel and gasoline powered automobiles operating in temperate or hot climates. Mobil 1 ESP Formula P 5W-30 has been expertly engineered to help prolong the life and maintain the efficiency of emission systems.

Mobil 1™ keeps your engine running like new!

Features and Benefits

Mobil 1 ESP Formula P 5W-30 is made with a proprietary blend of leading-edge components formulated to help provide exceptional cleaning power and wear protection, in conjunction with fuel economy benefits.

Features	Advantages and Potential Benefits
Low Ash, Sulphur, and Phosphorous content	Helps to reduce particulate build up in Diesel particulate filters and poisoning of gasoline catalytic converters
LSPI protection	Helps prevent destructive premature combustion events in gasoline turbocharged downsized engines
Active cleaning agents	Helps to reduce deposits and sludge build-up to enable long and clean engine life
Outstanding thermal and oxidation stability	Helps to reduce oil aging allowing extended drain interval protection and adequate engine protection and operation also in hot climate countries
Enhanced frictional properties	Aids fuel economy; allows meeting or exceeding the combined requirements of both ACEA C2 and C3
Excellent low temperature capabilities	Quick cold weather starting and fast protection to help extend engine life
Robust anti-wear properties	Helps protect engine parts such as timing chains, cams, tappets, cylinders subject to severe mechanical stresses

Applications

Mobil 1™ ESP Formula P 5W-30 carries recommendations for a wide range of passenger cars, SUVs and light vans. It is designed for modern high efficiency gasoline, diesel and hybrid cars from Stellantis (Peugeot, Citroën, Opel, Vauxhall, DS), Mercedes-Benz Group (MB, Smart) and General Motors (Chevrolet, Cadillac), as well as for Japanese and Korean vehicles that specifically call for a SAE 5W-30 viscosity grade and any of the specifications the oil supports.

Mobil 1 ESP Formula P 5W-30 has been fully qualified by Stellantis for 1.5L Blue HDi Diesel engines (DV5R engines) produced before February 2023 (FPW9.55535/03 approval) and for Stellantis cars operating in hot climates (PSA B 71 2297 approval).

Mobil 1 ESP Formula P 5W-30 is designed to be fully compatible with the latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's), and to deliver outstanding performance and protection making it the product of choice for vehicles operating under hot climates and allowing for extended oil change intervals where recommended by the manufacturer.

Owner's manual should be consulted for recommended viscosity grade and specification.

Specifications and Approvals

This product has the following approvals:
GM dexos2
MB-Approval 229.31
MB-Approval 229.51
MB-Approval 229.52
PSA B71 2290
PSA B71 2297
STELLANTIS FPW9.55535/03

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:
API SJ
API SL
API SM
API SN
ACEA C2
ACEA C3

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	64
Flash Point, Cleveland Open Cup, °C, ASTM D92	239
Pour Point, °C, ASTM D97	-48
Density @ 15 C, g/cm3, ASTM D4052	0.846

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Esso Société Anonyme Française

20 rue Paul Héroult

92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved